

Dipl.-Ing. (FH) Peter Kahlhorn Rambeeler Str. 6 23936 Upahl

E-Mail: info@kahlhorn.com Web: www.kahlhorn.com

UID: DE 174 168 707







Single-phase motorstarter 230V with emergency stop button

Manfacturer: Klinger & Born

Type: K3000/1Ph-230/Not-Aus/P

Product no.: 0099.3003 Weight: 1.600

■ Details

Ready-to-connect 1 phase AC motor starter with undervoltage release and emergency stop button.

■ Properties

- 2-pole switch (Contactor)
- Switching capacity up to 7,5 kW
- With undervoltage release
- With emergency stop button
- With connection cable, with CEE-Plug
- With splash water proof cover

■ Function

The switch is operated via on / off buttons. The emergency stop button switches the machine voltage free. It can only be switched on again after unlocking by turning the button.

■ Mounting

The switch is screwed to the machine via mounting lugs (order).

■ Specifications

Voltage Ue	230 V~
Contactor	KliBo7,5, 230V~ (Mod. 403657500)
Coil voltage Uc	230V~
Switching capacity	7,5 kW 230V~/AC-3
Type of actuation	Mechanically on/off
Connection motor side	1 m Cable H07RN-G 3 G1,5, stripped with cable lugs
Connection mains side	2 m Cable H07RN-G 3 G1,5 mit with earthed safety plug, 230 V.
Housing material	Polypropylene PP
Mounting position	any
Protection class	IP54, splash water proof



