

Dipl.-Ing. (FH) Peter Kahlhorn Rambeeler Str. 6 23936 Upahl UID: DE 174 168 707 E-Mail: info@kahlhorn.com Web: www.kahlhorn.com





Operating capacitor 12,5 µF / 450 V with flat plug

Manfacturer: Comar

Type: MKA 450-12.5 / FD Product no.: 125450MKP/FL

Weight: 0.080

Details

Capacitor with flat plug connection for the operation of single-phase AC motors, e.g. Of grinding machines, concrete mixers, wire rope hoists.

■ Construction

Metalized film capacitor inside a self-extinguishing plastic case (V2) with flat plug connection and base screw.

■ Note regarding voltage information

The voltage information refers to the dielectric strength and not the operating voltage. The capacitor can be used with a 230V AC motor.

■ Technical values according to EN 60252-1 (VDE560-8)

| Capacity | 12,5 μF ±5% nominal value |
|-----------------------|---|
| Nominal voltage | 450 V, 50-60Hz |
| Operating mode | Continuous operation |
| Operating temperature | -25° up to +85°C |
| Climate category | 25/85/21 |
| Application class | 400V - B 10000h (HPFNT) 450V - C 3000h (HPFPU) |
| Protection class | IP 00 |
| Connection | Flat pin connectors 6.3 mm |
| Housing dimensions | Ø35 x 70 mm |
| Base screw | M8 x 10 |

■ Please note

Capacitors have electrically 2 connections. Capacitors with 4 flat plugs have 2 flat plugs which are connected electrically.

The polarity does not matter when installing operating capacitors.