

Dipl.-Ing. (FH) Peter Kahlhorn Rambeeler Str. 6 23936 Upahl UID: DE 174 168 707



Operating capacitor 18 µF / 450 V, aluminium can, Flat plug

Manfacturer:HydraType:MAB MProduct no.:180400Weight:0.130

MAB MKP 18/500 180400MBA/FL 0.130

Details

Operating capacitor with flat plug connection for the operation of AC motors, e.g. Of small circular saws, lifting gearn.

Usable for continuous operation and intermittent operation

Construction

Self-healing capacitor (MKP) in aluminium housing with flat plug, overpressure protection, base screw

Note regarding voltage information

The voltage information refers to the dielectric strength and not the operating voltage. The capacitor can be used with a 230V AC motor.

Technical values

Capacity	18 μF
Capacity tolerance	±5% nominal value
Climate class	25/85/21 according to IEC 60068
Protection class	IP 00
Operating temperature	-25° up to +85°C (UL:-25°C)
Operating mode	Continuous operation or Intermittent operation AB 25% ED, SD 4h Intermittent operation AB 20% ED, SD 24h
Safety class	P2
Service life class	-25/+85°C: Class A - 30.000h - 420V (1-30 μF) Class B - 10.000h - 470V (1-30 μF); -420V (35-80 μF) Class C - 3.000h - 470V (35-80 μF) Class D - 1.000h - 500V (1,5-30 μF)
Mains frequency	50/60 Hz
Filling material	Environmentally friendly vegetable oil
Connection	4 x flat plug 6.3 mm
Housing Ø x length	35 x 98 mm
Base screw	M8 x 10

Security

Capacitors are wear parts, which fail under extreme conditions or at reaching their lifetime. Hydra motor capacitors are manufactured with a build-in overpressure disconnector. In case of failure, the capacitor will expand in the axial direction up to about 9 mm. Due to the expansion, the thinner section of the fuse will break and the capacitor will be disconnected safely from the mains.

Hydra capacitors are certified by the VDE Testing and Certification Institute and fulfill the regulations of



safety class P2 according to EN 60252.