



E-T-A circuit breaker 3120-F554-G7T1-W04D

Manufacturer:	E-T-A
Type:	3120-F554-G7T1-W04D
Product no.:	3120-F554-G7T1-W04D
Weight:	0.050

■ Details

2-pole insert switch with 1-pole thermal overload protection and splash water-/dust protection cover

■ Properties

- 2-pole off-switch
- With overcurrent protection
- With splash water proof cover IP54
- Rocker switch red with labelling 0-I
- Replacement for Weber Unimat WT 22-551 and WTN22-555 (refer to explanation)
- Replacement for Weber Protection ABTWFxxxCO (xxx = nominal current, z.B. 100 = 10.0A)

■ Important while replacing a Weber Unimat WT 22-551 or WT 22-555

This E-T-A switch is a suitable replacement for Weber Unimat WT 22-551 and WT22-555:

- Switch with 4 connections P1, P2, 3, 4. Connection 12(i) stays unoccupied
- Connection 3 without overcurrent protection and connection 5 without overcurrent protection

■ Dimensions

Installation opening	44.5 x 22 mm (clamping thickness 1-4 mm)
Collar height	2 mm with splash water proof cover IP54
Collar (cover)	50 x 27 mm with splash water proof cover
Installation depth	43 mm with connections

■ Specifications

Nominal voltage	AC 240 V; DC 50 V
Overload protection	Refer to nominal current-Auswahl
Protection class	Operating area IP54, connecting area IP00
Isolation	Reinforced in the actuation element
Ambient temperature	-30 . 60 °C
Switch	2-pole, 1-pole thermal protected
Approval	VDE, BV, CSA/UL, CCC
Installation	Snap-on frame
Connection	On the mains: clamp screw M3.5 and flat plug 6.3 mm Under load: flat plug 6.3 mm (2 x 2,8 mm)
Circuit breaker norm	EN 60934/IEC 60934: S-Typ, TO



