



## FTCAP starting capacitor 40 µF / 320 V

|               |                         |
|---------------|-------------------------|
| Manufacturer: | FTCAP Fischer & Tausche |
| Type:         | 40032036,8072           |
| Product no.:  | 40EL320                 |
| Weight:       | 0.200                   |

### ■ Details

starting capacitor for starting heavy-starting motors, e.g. Of compressors.

### ■ Important

The capacitor serves exclusively as a starting capacitor. It must not be used as an operating capacitor and must be switched off after the engine starts.o.

### ■ Construction

Cylindrical aluminum double housing with lateral 3-wire connection cable approx. 250 mm long, without base screw.

### ■ Operating mode

Intermittent operation AB 1.7% Duration 3 min. The duty cycle is a maximum of 1,7% of the total working cycle and corresponds to 20 evenly distributed 3-second intervals over one hour.

### ■ Technical values according to EN 60252-1 (VDE560-8)

|                                |                           |
|--------------------------------|---------------------------|
| <b>Capacity</b>                | 40 µF ±10% nominal value  |
| <b>Nominal voltage</b>         | 320V~ 50/60Hz             |
| <b>Operating mode</b>          | Intermittent operation AB |
| <b>Operating temperature</b>   | -10° up to +60°C          |
| <b>Protection class</b>        | IP 54                     |
| <b>Connection</b>              | Cable 250 mm 3G1,5        |
| <b>Dimensions (Ø x length)</b> | 37 x 69 mm                |