



## Emergency shut-off-main switch up to 7,5 kW with housing (Kedu ZH-C4)

Manufacturer: Klinger & Born  
Type: NHS-32  
Product no.: 45000240  
Weight: 0.350

### ■ Details

Main switch according to EN60204-1 up to 11.0kW 400V~/AC-23A+B

### ■ Properties

- Clear position indicator with 0 and I
- Contact separation by positively-opening contacts
- **Without undervoltage release**
- 4x cable inlet PG16 prepared
- Fixing: 80 x 80mm or 115mm
- With connecting clamps for N and PE
- Also usable as repair switch

### ■ Specifications

<b>Switching element</b>	3-pol., 32A according to EN60947-3
<b>Operating voltage</b>	500V~
<b>Thermal nominal current</b>	32A
<b>Short-circuit resistance</b>	Max. Insurance 35A (gL-characteristics)
<b>Connection cross section</b>	10.0qmm
<b>Connection screws</b>	M4
<b>Ambient temperature</b>	-25°C . +50°C
<b>Weight</b>	350g
<b>Operation</b>	3x lockable rotary knob, red on yellow base
<b>Housing (BxLxH)</b>	Without rotary knob: 100x126x71mm With rotary knob:100x126x105mm
<b>Colour</b>	Upper part: light grey Lower Part: dark grey
<b>Protection class</b>	IP54, splash water proof

### ■ Switching capacity

Voltage	AC-3	AC-23A	AC-21
3 x 230 V	5,5 kW	7.5 kW	32 A
3 x 400 V	7.5 kW	11.0 kW	32 A