

Dipl.-Ing. (FH) Peter Kahlhorn Rambeeler Str. 6 23936 Upahl UID: DE 174 168 707 E-Mail: info@kahlhorn.com Web: www.kahlhorn.com



# Switch-plug combination up to 3 kW with undervoltage release

Manfacturer:TripusType:204P960Product no.:SSK200Weight:0.300

# 


### Details

Switch-plug combination with zero voltage release for AC-motors up to 3 kW. the connection of the switch is made with the open base.

When the voltage drops, the switch actuates, therefore a connected device can not turn itself back on when the power recovers.

## **■** Properties

- 2-pole switch
- Switching capacity up to 3 kW
- With undervoltage release
- With connection possibility for thermal contact
- Including splash water proof cover
- Base open



# ■ Specifications

Voltage Ue	250 V~
Current le	13.5 A
Protection class	IP44
Switch	<u>Tripus 555.109</u> (with coil connection)
Switching capacity	3 kW
Connector	Safety plug (Type F, CEE 7/4 plug, CEE 7/7 plug)
Switch	2-pole
Type of actuation	Mechanically on/off
Mounting position	Any
Mounting dimensions	68 x 68 mm



### ■ Fitting capacitors, if required

Fitting capacitors can be found at the catalog "replacement parts" at Operating capacitor.

The right capacitor capacity can be found as specification in microfarad ( $\mu F$ ) on the capacitor or the type plate of the motor.