


Dipl.-Ing. (FH) Peter Kahlhorn Rambeeler Str. 6 23936 Upahl UID: DE 174 168 707







## Switch-plug combination up to 3 kW with motor protection

Manfacturer:	Tripus
Туре:	201.785
Product no.:	SSK510
Weight:	0.800

## Details

Universal usable switch-plug combination with overcurrent protection switch and undervoltage release. suitable for e.g. AC motor an circular saws, wood splitters, etc.

. . .

Properties

- 2-pole switch Switching capacity up to 3 kW
- With overcurrent protection
- With undervoltage release
- With under voltage release
- Including splash water proof cover

## Specifications

Voltage Ue	230 V~
Current le	13.5 A
Contactor	305.233
Switching capacity	3.0 kW 230V~
Type of actuation	Mechanically on/off
Connector	Safety plug (Type F, CEE 7/4 plug, CEE 7/7 plug),16A
Housing material	Polypropylene PP
Mounting position	Any
Protection class	IP54, splash water proof
Connection cable	1 m H07RN-F 3 G1,5
Mounting dimensions	68 x 68 mm
Tripus name	Model nr. 201.785, type KSVDW23.01

## Sold only to professional electrical companies

This switch requires the correct choice of the nominal current, therefore we only sell this switch to professional electrical companies.