


Dipl.-Ing. (FH) Peter Kahlhorn Rambeeler Str. 6 23936 Upahl UID: DE 174 168 707







Klinger&Born drill machine switch K900/ST12/R-0-L, Reversing switch

Manfacturer:	Klinger & Born
Туре:	K900/ST12/KA12/L-0-R
Product no.:	SSK912U
Weight:	0.700

Details

Ready-to-connect AC switch-plug combination with rotational direction switch e.g. For drilling machine, lathes, turning machines, etc.

The **Rotation direction switch** is located under the on-off-switch (refer to image). When operating the switch, 2 phases of the motor are switched therefore the rotation is changed.

Properties

- 3-pole switching on/off
- Switching capacity up to 9 A
- Undervoltage release
- With connection possibility for thermal contact
- Cam switch for Recht-/Linkslauf (Drehrichtungsänderung)
- With splash water proof cover, flap optional

Important

The rotation may only be changed, when the motor is on halt.

Installation / connection (refer to wiring diagram) / brake

The switch is screwed on the housing base. Grid dimension of the screws: 68 x 68 mm. Der cable outlet is steckerseitig im housingboden.

Specifications

Voltage Ue	400 V~
Current le	9,0 A
Switching capacity	4.0 kW 400V~, 9 A/AC-3
Type of actuation	Mechanically on/off
Connector	CEE 3P+N+E, 16A
Housing material	Polypropylene PP, shrouded plug PA
Mounting position	Any
Protection class	IP54, splash water proof
Connection cable	1 meter H07RN-F 5G 1,5
Mounting dimensions	68 x 68 mm
KliBo-Mod.	0098.3912



